

PREMITECO Infrared Touch Standing LCD Kiosk

Windows Powered | 10-Point Touch | Professional Interactive Solution





10-Point Infrared Touch



Floor-Standing Design



High-Quality Display



Durable Construction



Energy Efficient



Rich Connectivity





Key Features

- 10-Point Infrared Touch: Fast, accurate multitouch interaction
- Powerful Windows System: Intel Core i5 with 8GB RAM for smooth performance
- Floor-Standing Design: Ideal for interactive displays and self-service applications
- High-Quality Display: 55" FHD with 99% sRGB color accuracy
- Durable Construction: 7H tempered glass for scratch-resistant surface
- Rich Connectivity: Multiple USB, HDMI, VGA, and Ethernet ports
- Integrated Audio: Built-in dual speakers and optional array microphone
- Energy Efficient: ≤165W operation, ≤0.5W standby power



Display Performance

Display Specifications:

- Screen Size: 32-43-55-65-75-85 inch

- Resolution: 1920 × 1080 (FHD)

- Brightness: 300 cd/m²

- Contrast Ratio: 1200:1


- Color: 16.7M colors, 99% sRGB

- Viewing Angle: 89°/89°/89°/89°

- Response Time: 8ms (GtG)

- Panel Type: a-Si TFT-LCD

- Backlight: WLED, 50,000 hours lifespan







Touch Technology

Touch Specifications:

- Technology: Infrared Touch

- Touch Points: 10 points simultaneously

- Surface: 7H Tempered Glass, 92%

transmittance

- Accuracy: ±2mm

- Response Time: 8ms

- Durability: Virtually unlimited touches

- Input Methods: Finger or any non-transparent

object



Hardware & Performance

System Configuration:

- Operating System: Windows

- CPU: 8th Gen Intel Core i5

- RAM: 8GB DDR4

- Storage: 128GB SSD

- Graphics: Intel Integrated Graphics

- Motherboard: HM87 Chipset

Connectivity:

- HDMI × 1

- VGA × 1

- USB 3.0 × 2

- USB 2.0 × 2

- RJ45 Gigabit Ethernet


- Audio Input/Output

Media Support:

- Video: WMV, AVI, FLV, RM, RMVB, MPEG, TS, MP4, etc.

- Audio: MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc.

- Image: BMP, JPEG, PNG, GIF, etc.







Physical Specifications

Dimensions & Design:

- Unit Dimensions: $1900 \times 744.4 \times 43.6$ mm (H×W×D)
- Stand: Integrated floor-standing design
- Weight: Commercial grade construction

Audio & Accessories:

- Speakers: $2 \times 5W$ (8 Ω)
- Optional: Array microphone (custom order)

Quality & Support

Reliability Features:


- 50,000-hour display lifespan
- Industrial-grade construction
- Professional Windows platform
- Custom configuration available



Application Scenarios

Perfect For:

- Interactive Kiosks
- Digital Signage
- Self-Service Terminals
- Exhibition Displays
- Education & Training
- Corporate Lobbies
- Retail Environments
- Wayfinding Systems





Display			Infrared Touch Standi			
	32 "	43 "	55."	65 "	75"	85"
Size Panel Brands	BOE; CSOT; LG	BOE; CSOT; LG	BOE; CSOT; LG	BOE: CSOT;LG	BOE; CSOT; LG	BOE; CSOT; LG
or ands	Action and actions of	1920×1080 [FHD]	1920×1080 [FHD]	1920×1080 [FHD]	1920×1080 [FHD]	1920×1080 [FHD]
Niewable Size	69S. 4×392. S5mm	940. 896 × 529. 254mm	1209, 6×680. 4mm	1428.48×803.52mm	1660.8×934.2mm	1881.6×1058.4mm
15	89/89/89/89 (CR≫10)	89/89/89/89 (CR≫10)	39/89/89/89 (CR≫10)	39/89/39/39 (CR≥10)	89/89/89/89 (CR≥10)	39/89/89/89 (CR≥10)
Brightnes	300 cd/m2	300 cd/m2	300 cd/m2	300 cd/m2	300 cd/m2	300 cd/m2
Color	16.7M		16.7M	16.7M	16.7M	16.7M
Contrast	99% sRGB 1200:1 (Typ.) (TM)	99% sRGB 1200:1 (Typ.) (TM)	99% sRGB 1200:1 (Typ.) (TM)	99% sRGB 1200:1 (Typ.) (TM)	99% sRGB 1200:1 (Typ.) (TM)	99% sRGB 1200:1 (Typ.) (TM)
Ratio Response	Sms	Sms (199.7 (180	Sms	Sms	Sms	Sms
Time Screen	a-Si TFT-LCD	a-Si TFT-LCD			a-Si TFT-LCD	
Type Backlight			a-Si TFT-LCD	a-Si TFT-LCD		a-Si TFT-LCD
Type LCD Life	WLED 50000 hours	WLED 50000 hours	WLED 50000 hours	VLED	WLED 50000 hours	WLED 50000 hours
Touch				50000 hours		
Screen Size	32 7	43~	55 7	65 *	75*	85."
Touch Type	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared
Touch Screen Glass	Tempered glass (7H hardness, 92% transmittance)	Tempered glass (7H hardness, 92% transmittance)	Tempered glass (7H hardness, 92% transmittance)	Tempered glass (7H hardness, 92% transmittance)	Tempered glass (7H hardness, 92% transmittance)	Tempered glass (7H hardness, 92% transmittance)
Touch Points	10 points	10 points	10 points	10 points	10 points	10 points
Touch Me thod	Finger or non-transparent objects	Finger or non-transparent objects	Finger or non-transparent objects	Finger or non-transparent objects	Finger or non-transparent objects	Finger or non-transparent objects
	2mm	2mm	2mm	2mm	2mm	2mm
Touch Response	Sms	Sms	Sms	Sms	Sms	Sms
Speed Touch	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Times Operating System	Windows	Windows	Windows	Windows	Windows	Windows
Motherboa	HMS7	294S7	HMS7	HMS7	HMS7	HMS7
СРИ	Sth Gen Intel Core is	Sth Gen Intel Core is	Sth Gen Intel Core is	Sth Gen Intel Core i5	Sth Gen Intel Core is	Sth Gen Intel Core i5
RAM	SGB DDR4	SGB DDR4	SGB DDR4	SGB DDR4	SGB DDR4 SSD 12SGB	SGB DDR4 SSD 128GB
	SSD 129GB		SSD 129GB	SSD 128GB		
Graphics	Intel Integrated Graphics	Intel Integrated Graphics	Intel Integrated Graphics	Intel Integrated Graphics	Intel Integrated Graphics	Intel Integrated Graphics
I/O Interface s	HDMI × 1/VGA/USB3.0 × 2/USB2.0 × 2/RJ45 × 1/AUDIO	HDMI × 1/VGA/USB3.0 × 2/USB2.0 × 2/RJ45 × 1/AUDIO	HDMI × 1/VGA/USB3.0 × 2/USB2.0 × 2/RJ45 × 1/AUDIO	HDMI × 1/VGA/USB3.0 × 2/USB2.0 × 2/RJ45 × 1/AUDIO	HDMI × 1/VGA/USB3.0 × 2/USB2.0 × 2/RJ45 × 1/AUDIO	HDMI × 1/VGA/USB3.0 × 2/USB2.0 × 2/RJ45 × 1/AUDIO
Wired Network	1000M Ethernet	1000M Ethernet	1000M Ethernet	1000M Ethernet	1000M Ethernet	1000M Ethernet
Video	wav, zvi, flv, rm, rmvb, mpeg, ts, mp4, etc.	wav, zvi, flv, rm, rmvb, mpeg, ts, mp4, etc.	wav, zvi, flv. rm. rmvb. mpeg. ts. mp4, etc.	warv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc.	wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc.	wav, avi, flv, rm, rmvb, mpeg, ts, mp4, etc.
	MP2, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc.	MP2, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc.	MP2, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc.	MP2, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GFP, etc.	MP2, VMA, VAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc.	MP2, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc.
Image Support	BMP, JPBG, PNG, GIF, etc.	BMP, JPBG, PNG, GIP, etc.	BMP, JPBG, PNG, GIF, etc.	BMP, JPBG, PNG, GIF, etc.	BMP, JPBG, PNG, GIF, etc.	BMP, JPBG, PNG, GIP, etc.
•	External top (customized)	External top (customized)	External top (customized)	External top (customized)	External top (customized)	External top (customized)
Power Input	AC 100-240V 50/60 Hz	AC 100-240V 50/60 Hz	AC 100-240V 50/60 Hz	AC100-240V 50/60 Hz	AC 100-240V 50/60 Hz	AC 100-240V 50/60 Hz
Input Power Consumpti	≤16 5 ¥	≤165W	≤165W	≤165W	≤165W	≤165W
Standby Power	≤0.5¥	≤0. 5¥	≤0. 5T	≤0. 5W	≤0. 5V	≤0.5#
	Built-in S G 5W × 2 Speaker	Built-in SΩSW×2 Speaker	Built-in SΩSW×2 Speaker	Built-in SΩSW×2 Speaker	Built-in S G 5W × 2 Speaker	Built-in SΩ5W×2 Speaker
		Charles Asserted Section (Section Section Sect		popularistics and open the state of the stat	CONTRACTOR OF THE CONTRACTOR CONT	